



Specialty Products
and Insulation

Marine VBD 8847 Fiberglass Pipe Insulation

Description

Marine VBD 8847 jacketed fiberglass pipe insulation is composed of a molded, fiberglass insulation. SPI provides a durable, puncture resistant aluminum foil / scrim / metalized polyester facing vapor barrier. The fiberglass pipe covering is resilient and offers high thermal performance. The jacketed pipe insulation is typically used for shipboard hot and cold plumbing and mechanical systems but can be useful for other thermal or acoustical applications on pleasure craft, workboats, ferries, cruise ships, military vessels and offshore platforms. Other available Marine pipe insulation jackets include 59M and 002 AL Foil.

Specifications

* Approved as meeting Parts 2 and 5 of Annex 1 of the IMO FTP code (as tested for smoke and toxic gas generation and surface flammability) and is produced under lab follow-up services.

The base pipe covering is certified non-combustible by the U.S. Coast Guard per 164.109/70/0 and jacket system per 164.112/144/0.

Advantages

Thermal Insulation – This highly effective insulation system minimizes heat transfer and energy loss providing energy savings and a more comfortable environment.

System Durability – VBD 8847 insulation jacketing provides a highly durable insulation system with zero perm vapor barrier for superior condensation control.

Quality Control – Jacketed pipe insulation is produced in compliance with an established quality control program, under follow-up service with Intertek Testing Services NA Ltd., a qualified independent third party inspection agency. This ensures users of a consistent, high quality pipe insulation.

Installation

Marine VBD 8847 Fiberglass Marine pipe insulation is quick and easy to install with appropriate system insulation joint tape.

Availability

Standard Sizes: ½" to 6" ID., (Specify IPS, Copper or S.S.)
Standard Wall Thicknesses: ½", 1", 1 ½", 2", 2.5, 3"
Standard Length: 36" hinged sections

VBD 8847 Marine Fiberglass Pipe Insulation is available through SPI service centers nationally. Call or visit our website to locate one near you. www.spi-co.com



Performance Compliance Data

Jacket Material:

Color: Silver

Composition: Aluminum foil / scrim / metalized Polyester

Weight 0.019 lbs. / sq. ft.

UL 723: Flame spread < 25, Smoke Developed < 25

Permeance: per ASTM E96, 0.00 perm

Pipe Base Insulation Compliance: MIL-PRF-22344E

US Coast Guard/IMO: 64.109/70/0, Non Combustible

Service Temperature: per ASTM C411, 0-1000°F, (-18 to 538°C)

Density: per ASTM C302, (size dependent) 3.5 - 5.5 pcf


Thermal Conductivity: per ASTM C 518

Mean Temperature		Thermal Conductivity	
°F	°C	Btu·in/(hr·ft²·°F)	W/m·°C
75	25	0.23	0.034
250	150	0.32	0.051
500	275	0.54	0.082

ASTM E 84, UL723: 0 Flame Spread, 0 Smoke Developed

Sustainable Certifications: Certified by SCS services to contain an average of 53% recycled glass content, 31% pre and 22% post-consumer.

Note: properties as reported by manufacturer



1408/12

Marine VBD 8847 Fiberglass Pipe Insulation, Quote Request / Order Form

COMPANY	DATE
CONTACT	PHONE
PROJECT NAME & LOCATION	DATE REQUIRED
SHIP TO LOCATION	P.O. NUMBER

Marine VBD 8847 Fiberglass Pipe Insulation	Pipe Insulation (½", 1" 2", 2 ½", 3" thick, 3' Lengths)			
	Pipe Size	Thickness	Length	Sections
Foil Joint Tape, US Coast Guard Approved	Width 2, 3 or 4"		Roll	Quantity
Pipe Labels, System Names	Hot Water Supply	Domestic Cold Water	(Other)	(Other)
Label Quantity				

Note: Final quantities rounded to full carton or packaged quantities.



Disclaimer and Limitation of Warranty. The purchaser/user is advised to consult with the appropriate professionals and to read the manufacturer's product information to determine the adequacy or appropriateness of the product for the use intended. SPI makes no claim or representation regarding the use or applicability of the products. Further, SPI makes no warranty, expressed or implied, and disclaims all warranties including warranties of merchantability and fitness for a particular purpose.



**Specialty Products
and Insulation**

SPECIALTY PRODUCTS & INSULATION

2101 Rexford Road, Suite 300E

Charlotte, NC 28211

Phone: (855) 519-4044

Website: www.spi-co.com

E-mail: fabteam@spi-co.com

November 2019 - Form Marine VBD 8847 Pipe Insulation

**For additional information please
visit [http://www.spi-co.com/
literature.html](http://www.spi-co.com/literature.html)**

**Please ask your SPI Sales Representative
about other marine products and services.**